

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A forward position lighting device configured to be installed at a wing of an aircraft, the aircraft wing corresponding to a particular mounting platform, the device comprising:

a plurality of modular components, including

_____ a mounting module ~~on which having~~ one or more solid-state light sources ~~are mounted,~~

_____ a cut-off shield module that limits the light emitted by the solid-state light sources according to predetermined angular cut-off parameters, and

_____ a base assembly module including electronic circuitry that electrically connects the solid-state light sources to a power source within the aircraft,

wherein the modular components are configured so that the device is ~~operably compatible-mountable within the wingtip of multiple types of mounting platforms for aircraft wings without modifying the wingtip.~~

2. (Original) The device of claim 1, wherein the solid-state light sources are light-emitting diodes (LEDs), the LEDs being configured to emit at least one of aviation red and aviation green light.

3. (Currently Amended) The device of claim 2, further comprising:

a fastening mechanism configured to commonly fasten the mounting module to both the cut-off shield module and the wingtip configured to limit the light emitted by the LEDs according to predetermined angular cut-off parameters.

4. (Original) The device of claim 1, wherein the mounting module includes a heat sink.

5. (Original) The device of claim 4, the mounting module comprising a casting, wherein the heat sink comprises cooling fins incorporated in the casting of the mounting module.

Claim 6. (Canceled)

7. (Currently Amended) The device of claim-61, wherein the base assembly module is replaceable.

8. (Currently Amended) The device of claim-61, wherein the base assembly module is a type whose electronic circuitry is passive, the base assembly module being interchangeable with another type whose electronic circuitry is active.

9. (Currently Amended) The device of claim-61, wherein the base assembly module ~~is a type whose~~ includes electronic circuitry that is active, the active electronic circuitry being configured as a current control device for distributing a constant current to the solid state

light sources as the power source voltage fluctuates, the base assembly module being interchangeable with another type whose electronic circuitry is passive.

10. (Currently Amended) The device of claim-~~6~~1, wherein the base assembly module includes a heat sink.

11. (Original) The device of claim 10, the base assembly module comprising a casting, wherein the heat sink comprises cooling fins incorporated in the casting of the base assembly module.

12. (Currently Amended) The device of claim-~~6~~1, further comprising a fastening mechanism operable to fasten the mounting module to the base assembly module, and thereby fasten the device to the aircraft wing.

13. (Original) The device of claim 12, wherein the fastening mechanism includes at least one screw and corresponding clearance holes in the mounting module, base assembly module, and aircraft wing.

14. (Currently Amended) The device of claim 12, ~~further comprising:~~
~~— a cut-off shield module configured to limit the light emitted by the solid state~~
~~light sources according to predetermined angular cut-off parameters;~~

———wherein the cut-off shield module is fastened to the mounting module and base assembly module via the fastening mechanism.

15. (Original) The device of claim 1, the mounting module having dimensions, which are compatible with each of the multiple types of mounting platforms, thereby allowing the device to be mounted to the mounting platform without retrofitting the device or modifying the mounting platform.

16. (Currently Amended) A forward position lighting device utilizing light emitting diodes (LEDs), the device configured to be installed at a wing of an aircraft, the device comprising:

a mounting module including:

two side-emitting LEDs;

one or more reflectors operable to reflect at least a portion of light emitted by the side-emitting LEDs, the side-emitting LEDs and reflectors being configured so that the light emitted by the side-emitting LEDs and the light reflected by the reflectors combine according to a first distribution of light; and

a lambertian LED operable to emit light according to a second distribution of light,

wherein the lambertian LED is configured so that the first and second distributions of light combine to form a pattern of light, and

each side-emitting LED emits light around its optical axis such that radiant intensity peaks in the range of 60-100 degrees off the optical axis.

17. (Previously Presented) A forward position lighting device utilizing light emitting diodes (LEDs), the device comprising:

a mounting module including:

first and second LEDs;

one or more reflectors operable to reflect at least a portion of light emitted by the first and second LEDs, the first and second LEDs and reflectors being configured so that the light emitted by the first and second LEDs and the light reflected by the reflectors combine according to a first distribution of light; and

a third LED operable to emit light according to a second distribution of light, the third LED being a lambertian LED, wherein the third LED is configured so that the first and second distributions of light combine to form a pattern of light; and

a cut-off shield module operably connected to the mounting module, the cut-off shield module being configured to limit the pattern of light according to predetermined angular cut-off parameters.

18. (Original) The device of claim 17, wherein the cut-off shield module includes:

an overlap shield component configured to limit overlapping between the second distribution of light and another forward position light of the aircraft.

19. (Original) The device of claim 18, wherein the cut-off shield module includes:
- an auxiliary overlap shield component configured to limit overlapping between the first distribution of light and the other forward position light of the aircraft.
20. (Original) The device of claim 19, wherein the overlap shield and auxiliary overlap shield components provide angular cut-offs to the first and second distributions of light that correspond to predetermined maximum intensity requirements.
21. (Original) The device of claim 19, wherein the cut-off shield module includes:
- a perimeter shield component configured to limit overlapping between the pattern of light and a rear position light of the aircraft.
22. (Original) The device of claim 18, wherein an auxiliary overlap shield component is operably connected to the reflectors, the auxiliary shield component being configured to limit overlapping between the first distribution of light and the other forward position light of the aircraft.
23. (Original) The device of claim 18, wherein the dimensions of the mounting module and the cut-off module are compatible with each of a plurality of distinct mounting platforms, thereby allowing the device to be mounted to the distinct mounting platform without retrofitting the device or modifying the mounting platform.

24. (Original) The device of claim 16, wherein a shape of the reflectors is determined based on light-emitting characteristics of the side-emitting LED to produce the first distribution of light.

25. (Previously Presented) The device of claim 24, wherein each of the reflectors corresponds to one of the side-emitting LEDs, each of the reflectors including a curved reflective surface whose curvature is determined based on the light-emitting characteristics of the corresponding side-emitting LED to produce the first distribution of light.

26. (Previously Presented) The device of claim 24, wherein the shape of the reflectors is compatible with the light-emitting characteristics of both side-emitting LEDs that emit aviation red light, and side emitting LEDs that emit aviation green light.

27. (Original) The device of claim 16, wherein the dimensions of the device are compatible with multiple types of mounting platforms, thereby allowing the device to be mounted to each of the multiple types of mounting platform without retrofitting the device or modifying the mounting platform.

28. (Previously Presented) The device of claim 27, further comprising:

a base assembly module including electronic circuitry that electrically connects the lambertian and side-emitting LEDs to a power source within the aircraft, the base

assembly module being interchangeable with a base assembly modules with different electronic circuitry.

29. (Previously Presented) Then device of claim 28, wherein at least one of the mounting module and the base assembly module comprises a casting that incorporates cooling fins, the cooling fins being operable as a heat sink.